

Leica Piper 100 and 200 pipe lasers

Technical Data Sheet



Typical scope of delivery

Recommended Leica Piper package

- Leica Piper 100 or Leica Piper 200
- Rugged carrying case
- Remote control
- Target assembly
- Li-Ion battery
- Charger with AC and auto adapters
- Self-centering feet (150 mm/6 in)



Technical Data	Leica Piper 100	Leica Piper 200
Laser type	635 nm (red), laser class 3R	635 nm (red), laser class 3R
Laser output	4.75 mW maximum	4.75 mW maximum
Working range	200 m	200 m
Grade range	-10% to +25%	-10% to +25%
Self-levelling range	-15% to +30%	-15% to +30%
Line movement	6 m at 30 m	6 m at 30 m
Battery type	Lithium-Ion	Lithium-Ion
Operation/charge (dependant on environmental conditions)	40 h/4 h	40 h/4 h
Operating temperature range	-20°C to +50°C	-20°C to +50°C
Dimensions (diameter × length)	96 × 267 mm	96 × 267 mm
Weight	2 kg	2 kg
Construction	Cast aluminium	Cast aluminium
Protection class (splash water/dust proof)	IPX8	IPX8
Wireless remote	Front, up to 150 m Back, up to 10 m	Front, up to 150 m Back, up to 10 m
Alignmaster (autom. targeting system)	No	YES

- when it has to be **right**

Leica
Geosystems